

Our Main Aim Is To Provide Customized Solution To Meet Our Customers.
We Are Also Providing Service To All Brands.
We Will Be Happy To Serve You Within Shortest Period.

OUR PRODUCTS



CCTV



**FIRE
EXTINGUISHER**



**GOLD
MACHINES**



**IS YOUR HOME OR OFFICE IS SAFE &
SECURE WHEN YOU NOT PRESENT..??**



**CCTV Gives You Remote View
From Anywhere On Your Device
Through Internet Connectivity**

•CCTV•



•DVR•



•ROUTER•



•VDP•



•LCD•



ABC Powder

- ISI Mark
- Full range of spare parts are available
- Supplied with wall bracket
- Safe for use on live electrical equipment
- 1 Year warranty
- Squeeze grip operation
- Controlled discharge
- Fully refillable

Cylinder Material	M.S.
Capacity (KG)	1/2/4/6 & 9
Fire Rating	2A 8B/13B/21B/34B/55B
Extinguishing	Power
Temperature Range	-20C To +55C
Discharge Time (Sec)	More Than 08/13/Sec.
Discharge Range	More Than 02 Mtrs.
Test Pressure	35 Bar
Expellant	Nitrogen



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

DCP Powder

- ISI Mark
- Full range of spare parts are available
- Supplied with wall bracket
- Safe for use on live electrical equipment
- 1 Year warranty
- Squeeze grip operation
- Controlled discharge
- Fully refillable

Cylinder Material	M.S.
Capacity (KG)	4/6 & 9
Fire Rating	34B/55B/89B
Temperature Range	-20C To +55C
Discharge Time (Sec)	More Than 13/Sec.
Discharge Range	More Than 02 Mtrs.
Test Pressure	35 Bar
Expellant	Nitrogen



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

Co2 GAS

- ISI Mark
- Full range of spare parts are available
- Supplied with wall bracket
- Safe for use on live electrical equipment
- 1 Year warranty
- Controlled discharge
- Fully refillable

Cylinder Material	M.N.
Capacity (KG)	2/3/4.5
Fire Rating	8B/13B/21B
Extinguishing	Co2 Gas (IS15222)
Temperature Range	-20C To +55C
Discharge Time (Sec)	More Than 08/Sec.
Discharge Range	More Than 02 Mtrs.
Test Pressure	250 Bar



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

FOAM GAS

- ISI Mark
- Full range of spare parts are available
- Supplied with wall bracket
- Fully refillable
- 1 Year warranty
- Squeeze grip operation
- Controlled discharge

Cylinder Material	M.S.
Capacity (KG)	6 & 9 Ltr.
Fire Rating	34B/55B
Extinguishing	AFFF FOAM (IS4989)
Temperature Range	+5C To +55C
Discharge Time (Sec)	More Than 13/Sec.
Discharge Range	More Than 02 Mtrs.
Test Pressure	35 Bar
Expellant	Nitrogen/Co2



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

GOLD MACHINES



Make in India (Mumbai)

Model Number : SE0303

- Gold Melting furnace.
- Electronic temperature controls with digital displays.
- Small size, light weight, easy operation.
- High precision, fast heating, high efficiency
- Easy to replace spare parts
- Energy saving and environmental protection.
- Facility to set temperature
- Shock proof

Direct Melting furnace

Size	L	B	H
1)	235mm	x 200mm	x 410mm



Make in India (Mumbai)

Model Number : SE0304

- Gold Melting furnace.
- Electronic temperature controls with digital displays.
- Small size, light weight, easy operation.
- High precision, fast heating, high efficiency
- Easy to replace spare parts
- Energy saving and environmental protection.
- Facility to set temperature
- Shock proof
- Low voltage (transformer based)
- Power consumption..230 volts ..1200 watts .

Transformer Based Melter

Size	L	B	H
2)	460mm	x 240mm	x 350mm



Steam Machine



Ultrasonic Machine



GOLD PLATING RECTIFIER

SAFEPRO CLIENTS



022 2890 0600
081084 00600
096643 10466

Web: www.sonik.in
Email: sales@sonik.in